

AMENDMENT TO THE CLAIMS

1. (Previously Presented) A head suspension comprising:
 - a gimbal portion;
 - a load portion to exert a load force on a head assembly relative to a load point and the gimbal portion supporting the head assembly to roll about a roll axis;
 - a load portion to exert a load force on a head assembly relative to a load point and the gimbal portion supporting the head assembly to roll about a roll axis; andmeans for controlling roll attitude of the head assembly based upon a radial position of the head assembly in relation to a disc.
2. (Canceled)
3. (Previously Presented) A disc drive comprising:
 - a rotating disc mounted for rotation in the disc drive;
 - a head assembly;
 - a head suspension including a load portion adapted to supply a load force to the head assembly at a load point and a gimbal portion to allow the head assembly to pitch and roll relative to the load point;
 - an actuator coupled to the head suspension to move the head assembly relative to the disc; andmeans for dynamically controlling a roll attitude of the head assembly.

4. - 6. (Cancelled)

7. (Previously Presented) A head suspension comprising:

- a load portion to exert a load force on a head assembly relative to a load point;

- a gimbal portion having the head assembly coupled thereto to allow the head assembly to pitch and roll relative to the load point and the gimbal portion including opposed spaced gimbal beams on opposed sides of the load point; and

- a plurality of bending assemblies including a first bending assembly coupled to one of said gimbal beams and a second bending assembly coupled to another of said gimbal beams and the first and second bending assemblies being energizable to adjust pitch and roll attitudes of the head assembly.

8. (Previously Presented) The head suspension as claimed in claim 7, wherein the first bending assembly includes a first bending element energizable via a first electrical interface coupled to the first bending element and the second bending assembly includes a second bending element energizable via a second electrical interface coupled to the second bending element to independently energize the first and second bending elements to adjust the roll attitude of the head assembly.

9. (Previously Presented) The head suspension as claimed in claim 7, wherein:

- the first bending assembly includes a first bending element on the one of said gimbal beams and the second bending

assembly includes a second bending element on the other of said gimbal beams and the first and second bending elements are formed of a thermally expandable material forming a bi-metal structure having different coefficients of thermal expansion.

10. (Cancelled)

11. (Previously Presented) The head suspension as claimed in claim 7 wherein: the plurality of bending assemblies include a bending element formed of a piezoelectric material.

12. (Previously Presented) The head suspension as claimed in claim 7, wherein:

the first bending assembly includes a first bending element on the one of said gimbal beams and the second bending assembly includes a second bending element on the other of said gimbal beams and the first and second bending elements have an elongated length extending along an elongated length portion of the gimbal beams.

13. (Cancelled)

14. (Previously Presented) The head suspension as claimed in claim 8, wherein the first and second bending elements include opposed leading and trailing ends and the first and second electrical interfaces include opposed leads coupled proximate to the opposed leading and trailing ends of the first and second bending elements.

15. (Cancelled)

16. (Currently Amended) A head suspension comprising:

a ~~beam~~suspension portion to exert a load force on a head assembly relative to a load point;

a gimbal portion having the head assembly coupled thereto to allow a leading edge of the head assembly to pitch about a pitch axis and opposed sides of the head assembly to roll about a roll axis relative to the load point; and

the gimbal portion further including a plurality of bending elements including at least one bending element on a first side of the roll axis and at least one bending element on a second opposed side of the roll axis actuatable to adjust a roll attitude of the head assembly relative to the roll axis.

17. (Previously Presented) The head suspension as claimed in claim 16, wherein:

the plurality of bending elements are formed of a thermally expandable material forming a bi-metal structure having different coefficients of thermal expansion or a piezoelectric material.

18. (Previously Presented) The head suspension as claimed in claim 16, wherein:

the gimbal portion further comprises a pair of longitudinally extending gimbal beams and a connecting cross member between distal ends of the pair of gimbal

beams; and
the plurality of bending elements are mounted on the
connecting cross member.

19. (Cancelled)

20. (Previously Presented) The head suspension as claimed in claim 16, wherein:

the gimbal portion further comprises a pair of
longitudinally extending gimbal beams; and
the plurality of bending elements are mounted on the pair of
gimbal beams.

21. (Previously Presented) The head suspension as claimed in claim 16, wherein:

a first electrical interface is coupled to the at least one
bending element on the first side of the roll axis and
a second electrical interface is coupled to the at
least one bending element on the second opposed side of
the roll axis to independently energize the first and
second bending elements to adjust the roll attitude of
the head assembly.

22. - 33. (Cancelled)

34. (Previously Presented) The head suspension of claim 1
wherein the means for controlling the roll attitude includes a
plurality bending elements on opposed sides of the roll axis.

35. (Previously Presented) The head suspension of claim 34 wherein the plurality of bending elements are formed of a thermally expandable material forming a bi-metal structure having different coefficients of thermal expansion or a piezoelectric material.

36. (Previously Presented) The head suspension of claim 34 wherein the plurality of bending elements are independently energized relative to the radial position of the head assembly in relation to the disc.

37. (Previously Presented) The head suspension of claim 9 wherein the opposed spaced gimbal beams have a different coefficient of thermal expansion than the first and second bending elements to form the bi-metal structure having the different coefficients of thermal expansion.

38. (Previously Presented) The head suspension of claim 7 wherein the first and second bending assemblies are energized based upon a radial position of the head assembly relative to a disc.

39. - 45. (Cancelled)